



AMBANI ORGANIC PVT. LTD.

801 , 8th floor, "351 – ICON", Andheri (E), Mumbai – 400069 ,India

Tele – 022 26833778 www.ambaniorganics.com

AOPL 2504 Styrene Acrylic 50%

Chemical Type	: Styrene Acrylic
Appearance	: Milky White
Solid Content	: 50 +/- 1%
Viscosity @ 30°C by Brookfield RVT Spindale No 7 RPM 20	: 750 cps
pH	: 8 ~ 10
Free Monomer Content	: < 0.3%
Tg.	: 12 °C
Properties	: It has good wet and dry pick resistance, better heat and mechanical stability. Very good sheet gloss, smoother surface, improved opacity and brightness, improve Print gloss.
Recommended Applications	: Aopl 2504 is specialized fine particle size binder used for clay coating formulations. It is compatible with china clay, calcium carbonate, whiting, titanium dioxide and most other standard pigments. IT IS MAINLY USED FOR DUPLEX PAPER BOARD.

ISO: 9001 : 2008 Certified

The above information is to the best of our knowledge true and accurate. Since the conditions that the products are used in cannot be handled or controlled by us we cannot guarantee the results and assume liability to damages incurred by using this product
Refer to M.S.D.S. for handling procedures.