



## **AMBANI ORGANICS PVT. LTD.**

801, "351 – ICON", Andheri (E), Mumbai – 400069 ,India

Tele – 022 26833778 [www.ambaniorganics.com](http://www.ambaniorganics.com)

### **AOPL PS 3045 Styrene Acrylic 45%**

**Chemical Type** : Styrene Acrylic

**Visual Appearance** : Milky White

**Solid Content** : 45 +/- 2%

**Viscosity @ 30 °C**

**Brookfield RVT** : 1500 – 2000 c.Ps

**Spindale No 4**

**RPM 10**

**pH** : 8 ~ 10

**Free Monomer Content** : < 0.3%

**MFFT** : 18 °C

**Properties** : Forms a hard, tough, flexible and glossy film. Excellent wet scrub and abrasion resistant. Excellent pigment loading characteristics, alkali resistant. Can replace 50 % s/a by same volume.

**Recommended Applications** : For use in low cost washable distemper/ interior emulsion paints /cement primer. Can be use for economical exterior paint

#### **ISO: 9001 : 2008 Certified**

The above information is to the best of our knowledge true and accurate. Since the conditions that the products are used in cannot be handled or controlled by us we cannot guarantee the results and assume liability to damages incurred by using this product  
Refer to M.S.D.S. for handling procedures.