

Elscint Automation

W-191 Bhosari MIDC, Pune 411 026 Tel.: 27122059 Fax :+91-20-27122994 E-mail: sales@elscintautomation.com Website: www.elscintautomation.com

ELSCINTHANE BOWL COATINGS-

Elscinthane is a solvent borne sprayable urethane coating system based on aliphatic prepolymers and proprietary amine curatives. It has a proven durability as a premium grade abrasion and corrosion resistant material in many types of material handling situations. Particularly suited for small particle abrasion in wet environments, Elscinthane will provide years of dependable economic service.

Elscinthane is a two compound urethane coating packaged in proportioned kits for ease of application. Versatility is available in a wide variety of colours and additives for high build or Anti-Static properties, flame resistance and UV Stabilizers.

Applications:

Elscinthane can be applied through conventional air or airless spray equipment. As an aliphatic it can be applied in virtually any climate throughout the world. Application thicknesses range from 0.025 mm to 6 mm plus.

Smooth as well as rough coatings are possible with the help of a special process.

Properties –

Hardness: 90 (+/- 5) Shore A

Tensile Strength 4175 psi Elongation 320%

Tear Strength 450 lbs. Die C

Abrasion Resistance 36 gms / 1000 cycles / H 18 Wheels Ratio Part A – 100, Part B – 15 – by weight

Flash Point None

Priming System Elscintprime











GFW.

Elscint Automation

W-191 Bhosari MIDC, Pune 411 026 Tel.: 27122059 Fax :+91-20-27122994 E-mail: sales@elscintautomation.com Website: www.elscintautomation.com













