



## Safety bollards ASB

The new robust safety bollards for optimal protection.

### Features

- Spherical finish of the welded cap so that no water remains
- Available as a build-in model or with a foot plate
- Available in three different diameters

## Application

The new safety bollards protect doors, walls, loading and unloading areas, machinery and racks and are suitable for extreme loads. Also, the safety bollards are suitable for the protection of work areas.

The safety bollards are available as built-in and as a surface mounted model.

The built-in model is embedded 400mm in the concrete foundation or placed in a built-in device (casing). In that case, the bollard can be easily (temporarily) removed.

The surface mounted model is provided with a foot plate, which is provided with four mounting holes.

## Materials

The safety bollards are made out of galvanized metal tube and finished in a bright yellow colour (RAL 1023). At the top, the bollards poles are finished with a rounded convex cover welded to optimize the drainage of water.

### Model 1

Model 1 has a diameter of 76 mm and is suitable when the internal transport is a pallet-car. We recommend this model to place on walkways.



Article nr.	Length	Diam.	Thick-ness	Embed depth	Weight
ASB-1050	1230	76	3.6	300	14 kg
ASB-1051 (*)	940	76	3.6	n.v.t.	12 kg

(\*) surface mounted model provided with foot plate with mounting holes  
All dimensions in mm

### Model 2

Model 2 has a diameter of 168 mm and is suitable when the internal transport is a fork-lift truck. We recommend this model at openings in which a dock leveller is used for loading and unloading.



Article nr.	Length	Diam.	Thick-ness	Embed depth	Weight
ASB-1060	1230	168	4.5	300	54 kg
ASB-1061 (*)	940	168	4.5	n.v.t.	47 kg

(\*) surface mounted model provided with foot plate with mounting holes  
All dimensions in mm

### Model 3

Model 3 has a diameter of 270 mm and is suitable when a truck can drive into the building. We recommend this model for large openings where no dock leveller is used.



Article nr.	Length	Diam.	Thick-ness	Embed depth	Weight
ASB-1070	1230	270	5	300	80 kg
ASB-1071 (*)	940	270	5	n.v.t.	70 kg

(\*) surface mounted model provided with foot plate with mounting holes  
All dimensions in mm

## Options

Optional a mounting set for surface mounted safety bollards is available.