



Wheel guides AWG

Correct docking with wheel guides prevent damage.

Features

- Suitable for new and existing buildings
- Available as built-in or surface model in different dimensions
- Standard galvanized finish

Application

Wheel guides ensure correct positioning of the vehicle to the loading and unloading platform. Therefore the risk of damage to the vehicle, the building or the dock leveler, dock shelter reduces considerably. Wheel guides are especially recommended in combination with wide dock levellers, pillow or inflatable dock shelters because in these situations precise positioning of the vehicle is even more important.

The standard galvanized wheel guides are available as built-in and as a surface model. The built-in model is embedded in the concrete foundation. The surface mounted model is equipped with foot plates with mounting holes.

Surface mounted model (with foot plates)

Made from high quality tube with a diameter of 170 mm.

Available as:

- bended model (AWG-011)
- or straight model (AWG-012)



Article nr. (pair)	Length (mm)	Height (mm)	Diameter (mm)	Foot plate (mm)	Weight per pair (kg)
AWG-011	2000	320	170	200*200	102
AWG-012	1850	320	170	200*200	85

Built-in model (to embed into concrete foundation)

Made from high quality tube with a diameter of 170 mm.

. Available as:

- bended model (AWG-013)
- or straight model (AWG-014)



Article nr. (pair)	Length (mm)	Height (mm)	Diameter (mm)	Embed depth (mm)	Weight per pair (kg)
AWG-013	2000	320 (*)	170	520	109
AWG-014	1850	320 (*)	170	520	102

(*) na instorten

Low model (with foot plates)

Made from high quality tube with a diameter of 140 mm.

Available as:

- bended model (AWG-030)
- or straight model (AWG-025)



Article nr. (pair)	Length (mm)	Height (mm)	Diameter (mm)	Foot plate (mm)	Weight per pair (kg)
AWG-025	2000	188	140	175*135	60
AWG-030	1850	188	140	175*135	65

Options

Optional a mounting set is available for surface mounted wheel guides.