Lumitis LED Down Lights-M Series



Applications

- Offices, Malls, Showrooms, Hotels, Hospitals
- Meeting Rooms, Exhibitions, Conference Halls, Museums
- Residences

Features

- Can be used for retrofits as well as new projects
- No ballasts or chokes required.
- Excellent substitute for CFL Down Lights
- Elegant and Sleek
- All Lights manufactured with SMD design with latest technology
- Unique Heat sink design with high surface area for quick heat dissipiation
- Total isolated built in constant current drivers
- Aluminum body with PC Diffuser
- Consumes 60% to 70% less energy than conventional Lights
- No UV or RF interference
- No toxic substance like Mercury

Electrical Data

Input Voltage	AC 65V-265V/ 50Hz-60Hz	
Power Factor	> 0.9	
Driver Efficiency	>0.85	
THD	< 15%	

lumitis

Photometric Characteristics

Model Number	LM-DL-5W		
Power Consumption	5W		
Dimension (mm)	113 Dia X 114 Height		
Cut out (mm)	96		
Color Temperature	6000 – 70000K	2700 – 3500K	
Lumen Output	226 lm	173 lm	
Model Number	LM-DL-10W		
Power Consumption	10W		
Dimension (mm)	150 Dia X 137 Height		
Cut out (mm)	128		
Color Temperature	6000 – 7000K	2700 – 3500K	
Lumen Output	406 lm	365 lm	
Model Number	LM-DL-15W		
Power Consumption	15W		
Dimension (mm)	173 Dia X 165 Height		
Cut out (mm)	156		
Color Temperature	6000 – 7000K	2700 – 3500K	
Lumen Output	593 lm	563 lm	
Beam Angle	80 – 100 Deg		
Color Rendering Index	> 85a		
Installation	Indoor		
Material	Aluminum Alloy + PC Diffuser		
Colors	Pure White	Warm White	
Working temperature	Less than 60 DegC		
Effective life time	50,000 hours – 70% lumen maintenance		
Warranty	2 Years		

<u>Notes</u>

- In case you are replacing a CFL Down light, please ensure Ballast is removed before installing the LED Down Light.
- Please contact us for other sizes & wattages
- The design & specifications are subject to change with out prior notice

TIS Power Solutions

(Division of Techexpress Industrial Supplies Pvt. Ltd) #317, BPS Plaza, Mulund(West), Mumbai – 400080 Tel: 022-25914353 Email : <u>admin@techexpress.co.in</u>