Lumitis LED MR16/GU10 Lights-E Series



Applications

- Offices, Malls, Showrooms, Hospitals
- · Meeting Rooms, Exhibitions, Conference Halls, Hallway,
- Hotels, Restaurant lobby, Casino, Museums

Features

- Can be used for retrofits as well as new projects
- Excellent substitute for MR16/GU10 Halogen Lamps
- Elegant and Compact
- All Lights manufactured with SMD design with latest technology
- Unique sectional thermal material for quick heat dissipation
- Total isolated built in constant current drivers
- Aluminum body
- Consumes 80% to 90% less energy than conventional Lights
- No UV or RF interference
- No toxic substance like Mercury

Electrical Data

Input Voltage	AC 85V-265V, 12V, 24V
Power Factor	> 0.85
Driver Efficiency	>0.85
THD	< 15%

lumitis

Photometric Characteristics

Model Number	LE-MR-3W	
Power Consumption	3W	
Dimension (mm)	50mm Dia X 56mm Height	
Color Temperature	3000 – 3500K	6000 – 6500K
Lumen Output	120 lm	160 lm
Model Number	LE-MR-4W	
Power Consumption	4W	
Dimension (mm)	50mm Dia X 56mm Height	
Color Temperature	3000 – 3500K	6000 – 6500K
Lumen Output	240 lm	380 lm
Model Number	LE-MR-6W	
Power Consumption	6W	
Dimension (mm)	50mm Dia X 58mm Height	
Color Temperature	3000 – 3500K	6000 – 6500K
Lumen Output	375 lm	460 lm
Model Number	LE-MR-8W	
Power Consumption	10W	
Dimension (mm)	50mm Dia X 80mm Height	
Color Temperature	3000 – 3500K	6000 – 6500K
Lumen Output	415 lm	510 lm
Beam Angle	30, 40, 60 Deg	
Installation	Indoor	
Material	Aluminum Alloy	
Base	MR16/GU10	
Colors	Warm White	Pure White
Working temperature	-20°C~50°C	
Effective life time	50,000 hours – 70% lumen maintenance	
Warranty	2 Years	

Notes

- Please contact us for other sizes & wattages
- The design & specifications are subject to change with out prior notice

TIS Power Solutions

(Division of Techexpress Industrial Supplies Pvt. Ltd) #317, BPS Plaza, Mulund(West), Mumbai – 400080 Tel: 022-25914353 Email: admin@techexpress.co.in

www.lumitisledlights.com