

# TRANSPower® SWITCHGEAR INDUSTRIES

E-mail : [transp@mtnl.net.in](mailto:transp@mtnl.net.in) / [transp@vsnl.com](mailto:transp@vsnl.com) • [www.transpowerindia.com](http://www.transpowerindia.com)

Tel. : (0) 2512 5237 / 2510 7952 • Fax : 2502 2170

Mob. : 9820539902 / 9820351340 / 9920539902

## WATER CO<sub>2</sub> TYPE FIRE EXTINGUISHER

Suitable for A class of fire involving carbonaceous materials such as Paper, Wood, Clothes, Plastics etc.

Extinguishing agent	Water Cooling		
Available capacity in ltrs.	9	50	150
IS Specification	940	13385	13385
Jet range in mtrs.	6	10	20
Discharge time in secs.	60 - 120	60 - 180	60 - 180



## MECHANICAL FOAM (AFFF) TYPE FIRE EXTINGUISHER

Suitable for A & B class of fire involving Paper, Wood, Clothes, Plastics etc. Petrol, Oil, Paints, Thinner, Spirits etc.

Extinguishing agent	Foam Blanketing		
Available capacity in ltrs.	9	50	150
IS Specification	10204	13386	13386
Jet range in mtrs.	6	10	16
Discharge time in secs.	25 - 90	60 - 180	60 - 180



## DRY POWDER TYPE FIRE EXTINGUISHER

Suitable for B & C class of fire involving Petrol, Oil, Paints, Thinner, Spirits, Flammable Gases & Electrical fires etc.

Extinguishing agent	Dry Powder Blanketing					
Available cap. in kgs.	1, 2	5	10	25	50	75
IS Specification	2171			10658		
Jet range in mtrs.	2	4.5	6	6	8	10
Discharge time in secs.	8-10	15-20	23-30	25-30	40-50	50-60



## CO<sub>2</sub> TYPE FIRE EXTINGUISHER

Suitable for B & C class of fire involving Petrol, Oil, Paints, Thinner, Spirits, Flammable Gases & Electrical

Extinguishing agent	CO <sub>2</sub> Gas Blanketing					
Available capacity in kgs.	1, 2	3	4.5	6.5	9	22.5
IS Specification	2878					
Jet range in mtrs.	2	2	2-5	2.5-3	2.5-3	2.5-3
Discharge time in secs.	14-16	16-18	20-24	25-30	25-35	50-60



## ABC DRY POWDER TYPE FIRE EXTINGUISHER

Suitable for A, B & C class of fire involving Paper, Wood, Clothes, Plastics etc. Petrol, Oil, Paints, Thinner, Spirits etc. Flammable Gases, Electrical fires etc.

Extinguishing agent	Dry Powder Blanketing		
Available capacity in kgs.	1, 2	5	10
IS Specification	13849		
Jet range in mtrs.	4	4	4
Discharge time in secs.	8-10	15-20	20-30



## ABC MODULAR TYPE AUTOMATIC FIRE EXTINGUISHER

Suitable for A, B & C class of fire involving Paper, Wood, Clothes, Plastics etc. Petrol, Oil, Paints, Thinner, Spirits etc. Flammable Gases, Electrical fires etc.

Extinguishing agent	Dry Powder Blanketing		
Available capacity in kgs.	5	10	15
Discharge time in secs.	3	5	8



## CO<sub>2</sub> GAS CARTRIDGES

### FOR USE IN FIRE EXTINGUISHERS

Available Capacity  
30 / 60 / 120 / 200 / 300 / 500 Gms.

